



20266084



## Thermostat, change-over contact, with centre plate Berker Q.1/Q.3/Q.7/Q.9

### Technical features

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz

#### Electric current

Switching current "Heating" at $\cos \varphi = 0.6$	4 A
Heating switching current	10 A
"Switching current "Cooling" at $\cos \varphi = 0.6$ "	2 A
"Switching current "Cooling""	5 A

#### Measurement

Range of temperatures	5 / 30 °C
-----------------------	-----------

#### Materials

Colour of design line	aluminium
Colour	aluminium
Material / workmanship	lacquered
Material	Plastic/metal

#### Installation, mounting

Installation mode	without spreader claws
-------------------	------------------------

#### Connection

- with plug-in terminals

#### Equipment

Switching temperature difference	≈ 0,5 K
<ul style="list-style-type: none"> <li>- for heating or cooling mode</li> <li>- setting knob with temperature range limitation</li> <li>- e.g. for valve drives closed in de-energised state</li> </ul>	

#### Use conditions

Energy efficiency class	I (1%)
- with thermal return	

#### temperatur

Temperature	5...30 °C
-------------	-----------

#### Identification

Application, usage	HVAC control
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9