




47580002



SCHUKO socket outlet with hinged cover with labelling field, enhanced contact protection, Mounting orientation variable in 45° steps, Berker Arsys, gold matt, aluminium anodised

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Central cover plate
- when opening hinged cover, it can be arrested in end position	

Materials

Design lines special colours	gold
Colour	gold
Colour	gold optics
RAL colour	RAL 1004 - Golden yellow
Material / workmanship	aluminium, anodised
Material	Aluminium
Surface appearance	matt

Dimensions

Insertion depth	32 mm
-----------------	-------

Installation, mounting

Installation mode	mounting orientation of insert selectable in 45° steps, with spreader claws
-------------------	---

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Use

Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 2 - Sales	enhanced contact protection
Differentiation characteristic 3 - Sales	Mounting orientation variable in 45° steps

Safety

IK protection code against mechanical impacts	02
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

Identification

Main design line	Berker Arsys
------------------	--------------

Instructions

Information text	Specially suited to combinations of several socket outlets if right angle plugs are used. 1140.
	Labelling field height designed for 6 mm P-touch strips.
