




30863515



Control change-over switch insert, rocker surface-mounted/flush-mounted with lens, Berker W.1, grey matt

Technical features

Architecture

Type of control unit	single rocker
Fixing mode	flush-mounting or surface-mounting

Configuration

- Change-over

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

Electric current

Switching current	10 AX
-------------------	-------

Materials

Colour of design line	grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	matt

Dimensions

Depth	42 mm
Height	70 mm
Width	70 mm

Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

Connection

Type of connection	Quickconnect
- with plug-in terminals - with N-terminal	

Cable

- with cable entry at top and bottom

Equipment

- with 230 V LED unit
- for monitoring circuit

Use

Differentiation characteristic 2 - Sales	with lens
--	-----------

Safety

Protection index IP	IP55
---------------------	------

Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

Identification

Main design line	Berker W.1
------------------	------------

Instructions

Information text	Pins of quick-release lock made of ZAMAK
- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.	