



50413515



Push-button insert, NO contact with rocker surface-mounted/flush-mounted with labelling field - illuminated, Berker W.1, grey matt

Technical features

Architecture

Type of control unit rocker

Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

Electric current

Momentary-contact current 10 A

Materials

Colour of design line grey

Colour iron grey

Colour dark grey

RAL colour RAL 7011 - Iron grey

Material thermoplastic

Surface appearance matt

Dimensions

Depth 42 mm

Labelling field (W x H) 50 x 16 mm

Height 71 mm

Width 71 mm

Installation, mounting

Installation mode for screw fastening

Connection

- Wago clip-in 3-wire connection terminal for wiring
- with N-terminal
- with plug-in terminals

Cable

- with cable entry at top and bottom

Equipment

- with (b blue) 230 V LED unit

Use

Differentiation characteristic 1 - Sales with labelling field - illuminated

Safety

Protection index IP IP55

Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

Information text	Pins of quick-release lock made of ZAMAK, For labelling with name, information notice, etc., Labelling field height arranged for P-touch strips 12 mm.
------------------	--

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.
-