



47403523



IP55

SCHUKO socket outlet with green hinged cover surface-mounted Berker W.1, grey/light grey matt

Technical features

Architecture

| | |
|-------------|------------------------|
| Design | according to DIN 49440 |
| Fixing mode | surface-mounting |

Configuration

- ample room for wiring under the bases of the inserts

Connectivity

| | |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Electric current

| | |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

Cover, door

| | |
|---|------------------|
| Cover | Complete housing |
| - with hinged cover that falls back, manual clip-in | |

Materials

| | |
|-----------------------|----------------------|
| Colour of design line | grey/light grey |
| Colour | light grey |
| Colour | dark grey |
| RAL colour | RAL 7011 - Iron grey |
| Material | thermoplastic |
| Surface appearance | matt |

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | for screw fastening |
|-------------------|---------------------|

Connection

| | |
|---|---------------------------------|
| Connection terminals | according to IEC 60884-1 |
| Connection terminals | according to VDE 0620-1:2021-02 |
| - with Wago clip-in 2-wire connection terminal for wiring | |
| - with two clip-in places for Wago 2-wire connection terminals in the housing floor | |
| - with plug-in terminals | |

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Safety

IK protection code against mechanical impacts 05

Protection index IP IP55

- without enhanced contact protection

Use conditions

Operating temperature -40...30 °C

Storage/transport temperature -50...50 °C

Identification

Application, usage Surface-mounted wet-room installation

Main design line Berker W.1

Instructions

Information text Hinged cover springs made of stainless steel, pins
of quick-release lock made of ZAMAK
