



6768777106





Socket outlet with earthing pin and hinged cover with enhanced touch protection, Berker K.1, anthracite matt, lacquered

Technical features

| Arc | | |
|-----|--|--|
| | | |
| | | |
| | | |
| | | |

| Fixing mode | flush-mounting |
|-----------------|----------------|
| - 2pole + earth | |

Main electrical features

| Nominal voltage | 250 V |
|-----------------|----------|
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Cover, door

| Cover | Central cover plate |
|---|---------------------|
| - when opening hinged cover, it can be arrested in end position | |

Materials

| anthracite |
|--------------|
| a |
| arcoal grey |
| - Black grey |
| lacquered |
| ermoplastic |
| matt |
| |

Dimensions

| Insertion de | epth | 31.2 mm |
|--------------|------|---------|
| | | |

Installation, mounting

| Installation mode | with | spreade | er cl | aws |
|-------------------|------|---------|-------|-----|
|-------------------|------|---------|-------|-----|

Connection

| Connection terminals | according to IEC 60884 | | |
|--------------------------|------------------------|--|--|
| - with plug-in terminals | | | |

Use

Safety

| IK protection code against mecanical impacts | 05 |
|--|--------------------------|
| Enhanced contact protection | according to IEC 60884-1 |
| - Enhanced contact protection | |

Identification

| Main design line | Berker K.1 |
|------------------|------------|
|------------------|------------|