


47357006



IP20

SCHUKO socket outlet with enhanced touch protection, Berker K.1, anthracite matt, lacquered

Technical features

Architecture

Design according to DIN 49440

Fixing mode flush-mounting

Connectivity

Type of USB port other

Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

Frequency 50/60 Hz

Rated current 16 A

Electric current

Rated current 16 A

Cover, door

Cover Central cover plate

Materials

Colour of design line anthracite

Colour anthracite

Colour anthracite charcoal grey

RAL colour RAL 7021 - Black grey

Material / workmanship lacquered

Material thermoplastic

Surface appearance matt

Dimensions

Insertion depth 32 mm

Installation depth, flush-mounted boxes 31 mm

Installation, mounting

Installation mode with spreader claws

Connection

Connection terminals according to IEC 60884-1

Connection terminals according to VDE 0620-1:2021-02

- with plug-in terminals

Use

Differentiation characteristic 2 - Sales with enhanced touch protection

Safety

IK protection code against mechanical impacts	05
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

Identification

Main design line	Berker K.1
------------------	------------
