



50753505



**IP55**

**Blind series push-button with imprinted symbol arrow surface-mounted Berker W.1, grey/light grey matt**

Technical features

**Configuration**

- with mechanical and electrical interlock to prevent mutual activation

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC

**Electric current**

Momentary-contact current	10 A
---------------------------	------

**Materials**

Colour of design line	grey/light grey
Colour	iron grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	matt

**Installation, mounting**

Installation mode	for screw fastening
-------------------	---------------------

**Connection**

- with Wago clip-in 2-wire connection terminal for wiring
- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with plug-in terminals

**Cable**

- with one entry for 2 cables and one entry for cable and tube

**Equipment**

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

**Safety**

Protection index IP	IP55
---------------------	------

**Use conditions**

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

**Identification**

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

**Instructions**

Information text	Pins of quick-release lock made of ZAMAK
------------------	--