


47452089



**SCHUKO socket outlet Mounting orientation variable in 45° steps, Serie R.classic, polar white glossy**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Central cover plate
-------	---------------------

**Materials**

Colour of labelling	105,105,105
Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Material for printing	ASA polar white
Surface appearance	glossy

**Dimensions**

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

**Installation, mounting**

Installation mode	with spreader claws
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

**Equipment**

Type of configuration	Laserdruck
-----------------------	------------

**Use**

---

Differentiation characteristic 3 - Sales	Mounting orientation variable in 45° steps
--	--

---

**Safety**

---

IK protection code against mechanical impacts	05
---	----

---

Protection index IP	IP20
---------------------	------

---

- without enhanced contact protection

---

**Identification**

---

Main design line	Serie R.classic
------------------	-----------------

---