



13293512

Frame 2gang vertical for flush-mounted installation with sealing, Berker W.1, polar white matt

Technical features

Architecture

| | |
|-------------------|----------------|
| Technical version | 2gang vertical |
|-------------------|----------------|

Capacity

| | |
|-------------------|---|
| Number of sockets | 2 |
|-------------------|---|

Materials

| | |
|---------------------------|-----------------------|
| Colour of design line | polar white |
| Colour | polarwhite |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Material | thermoplastic |
| Surface appearance | matt |
| Type of surface treatment | untreated |

Dimensions

| | |
|--------|--------|
| Depth | 23 mm |
| Height | 154 mm |
| Width | 83 mm |

Installation, mounting

| | |
|-------------------|--|
| Installation mode | for flush-mounted and hollow-wall mounting, with mounting adapter and sealing, for vertical mounting, with clamp/screw fastening |
|-------------------|--|

Use

| | |
|--|--------------|
| Differentiation characteristic 2 - Sales | with sealing |
|--|--------------|

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

Use conditions

| | |
|-------------------------------|-------------|
| Operating temperature | -40...30 °C |
| Storage/transport temperature | -50...50 °C |

Identification

| | |
|--------------------|-------------------------------------|
| Application, usage | Flush-mounted wet-room installation |
| Main design line | Berker W.1 |

Instructions

- The degree of protection IP55 will only be reached if mounted with a modular flush-mounted insert of the Berker W.1 product line