product sheet 20300001





Protection



| Functions | |
|--|---|
| - with on/off switch and indicator LED for "on" | |
| Main electrical features | |
| Nominal voltage | 250 \ |
| Rated voltage | 250 V A0 |
| Frequency | 50/60 H: |
| Electric current | |
| Inductive load at $\cos \varphi$ = 0.6 | max. 4 A |
| Switching current "Heating" at $\cos \phi = 0.6$ | 4 / |
| Heating switching current | 10 / |
| Switching current | 10 / |
| Measurement | |
| Range of temperatures | 5 / 30 °C |
| Materials | |
| Colour of design line | brow |
| Colour | brow |
| Material | Plastic/meta |
| Dimensions | |
| Insertion depth | 24,5 mn |
| Installation, mounting | |
| Installation mode | without spreader claws |
| Connection | |
| Connection | with separate connection for night lowering |
| - with plug-in terminals | |
| Equipment | |
| Night lowering | ≈ 4 |
| Switching temperature difference | ≈ 0,5 I |
| setting knob with temperature range limitation e.g. for valve drives closed in de-energised state | |
| Use | |
| Differentiation characteristic 1 - Sales | with rocker switcl |
| Use conditions | |
| Energy efficiency class | I (1% |
| - with thermal return | |

Temperature controller, NC contact, with centre plate with rocker switch, Berker Arsys, brown glossy

Technical subject to change



| temperatur | |
|--------------------|--------------|
| Temperature | 530 °C |
| Identification | |
| Application, usage | HVAC control |
| Main design line | Berker Arsys |