



47231909



**SCHUKO socket outlet with enhanced touch protection, Berker S.1/B.3/B.7, polar white matt**

**Technical features**

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Central cover plate
-------	---------------------

**Materials**

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

**Dimensions**

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

**Installation, mounting**

Installation mode	with clamp/screw fastening
-------------------	----------------------------

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

**Equipment**

With transparent product label holder	no
---------------------------------------	----

**Use**

Differentiation characteristic 2 - Sales	with enhanced touch protection
--	--------------------------------

### Safety

IK protection code against mechanical impacts	05
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

### Identification

Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7