



3315416082



## VGA socket outlet with screw-in lift terminals

### Technical features

#### Connectivity

- with straight outlet
- S-VGA compatible
- with 15pole D-subminiature jack (front)

#### Frequency

Frequency range video max. 160 MHz

#### Screen

Resolution max. 1280 x 1024 px

#### Materials

Colour of design line white  
 RAL colour RAL 1013 - Oyster white  
 Material Plastic/metal  
 Surface appearance velvety

#### Installation, mounting

Installation mode without spreader claws

#### Connection

Conductor cross-section max. 1,5 mm<sup>2</sup>

- with screw-in lift terminals for connection to 15-core VGA cable

#### Equipment

- with supporting ring

#### Use

Differentiation characteristic 3 - Sales with screw-in lift terminals

#### Identification

Secondary design line(s) Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

#### Instructions

##### Information text

For connecting PCs, notebooks, etc. to display devices such as monitors (including LCD monitors) and projectors., Observe the instructions of the cable and device manufacturers for maximum VGA cable lengths!, Fränkische: "Multimedia tube" for laying pre-assembled connection cable, Art. no. 294.10.092, Installation recommendation: Kaiser: "Electronic box" for compliance with the permissible bending radii, Art. No. 1068-02 or 9062-74