



6167331404



**Socket outlet without earthing contact with enhanced touch protection, Berker S.1/B.3/B.7, aluminium, matt, lacquered**

#### Technical features

#### Architecture

Fixing mode	flush-mounting
- 2pole	

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Colour of design line	aluminium
Colour	aluminium
Colour	aluminium optics
RAL colour	RAL 9006 - White aluminium
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	matt

#### Dimensions

Insertion depth	32 mm
Mirror depth	8 mm

#### Installation, mounting

Installation mode	without spreader claws, for screw fastening
-------------------	---

#### Connection

Connection terminals	according to IEC 60884-1
- with plug-in terminals	

#### Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
--	--------------------------------

#### Safety

IK protection code against mechanical impacts	05
Enhanced contact protection	according to IEC 60884-1
- Enhanced contact protection	

#### Identification

Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7