



47432045



**SCHUKO socket outlet Berker R.1/R.3/R.8, black glossy**

**Technical features**

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Central cover plate
-------	---------------------

**Materials**

Colour of labelling	217,217,217
Colour of design line	black
Colour	black
Colour	deep black
RAL colour	RAL 9005 - Jet black
Material	thermoplastic
Material for printing	PC-PMA black
Surface appearance	glossy

**Dimensions**

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

**Installation, mounting**

Installation mode	with spreader claws
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

**Settings**

Shading parameter	R1_czarny
Laser parameter	R1_schwarz

#### Equipment

Type of configuration	Laserdruck
-----------------------	------------

#### Safety

IK protection code against mechanical impacts	05
Protection index IP	IP20
- without enhanced contact protection	

#### Identification

Main design line	Berker R.1/R.3/R.8
Secondary design line(s)	Berker R.1, Berker R.3, Berker R.8