




41436084



SCHUKO socket outlet with screw-in lift terminals, Berker Q.1/Q.3/Q.7/Q.9

Technical features

Architecture

Design according to DIN 49440

Fixing mode flush-mounting

Connectivity

Type of USB port other

Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

Frequency 50/60 Hz

Rated current 16 A

Electric current

Rated current 16 A

Cover, door

Cover Central cover plate

Materials

Colour of design line aluminium

Colour aluminium

Colour aluminium optics

RAL colour RAL 9006 - White aluminium

Material / workmanship lacquered

Material thermoplastic

Surface appearance velvety

Dimensions

Insertion depth 32 mm

Installation depth, flush-mounted boxes 31 mm

Installation, mounting

Installation mode with spreader claws

Connection

Connection terminals according to IEC 60884-1

Connection terminals according to VDE 0620-1:2021-02

- with screw-in lift terminals

Use

Differentiation characteristic 3 - Sales with screw-in lift terminals

Safety

IK protection code against mechanical impacts	02
Protection index IP	IP20
- without enhanced contact protection	

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9
