


294810



Time relay insert Light control

Technical features

Controls and indicators

- is switched off when actuated in the switched-on state

Main electrical features

Nominal voltage	240 V
Frequency	50/60 Hz

Electric current

Rated current	6 A
---------------	-----

Fuse

Fuse	short-circuit and overload proof (fine-wire fuse), with spare fuse
------	--

Power

Conventional transformers	1000 VA
Electronic transformers	1500 W

Measurement

Extension unit input	with extension unit input for push-button (NO contact)
----------------------	--

Materials

Colour	not applicable
Material	Plastic/metal

Dimensions

Insertion depth	32,5 mm
Axis dimension Ø	4 mm

Lighting control

- uncompensated	500 VA
-----------------	--------

Fluorescent bulbs control

Fluorescent lamps in duo circuit	1000 VA
Fluorescent lamps parallel compensated	150 VA

LED control

LED	with red control LED
-----	----------------------

Incandescent bulbs control

230 V incandescent lamps	1500 W
230 V halogen lamps	300 W

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Settings

Delay time, adjustable	≈ 1 mn...1 h
------------------------	--------------

Equipment

-
- very low noise
 - electronic timer with on/off pressure switch
-

Identification

Application, usage	Light control
Main design line	Light control
