



75441371



IP20

KNX CO² sensor with humidity and temperature regulation with integral bus coupling unit, KNX - Berker K.1/K.5

Technical features

Architecture

Fixing mode flush-mounting

Functions

Operating mode Operating modes: comfort, standby, night lowering, frost/heat protected

- Binary input functions: switching, dimming, blind, value transmitter, light scene extension unit
- Binary inputs can be blocked in operation

Controls and indicators

- with programming button and red programming LED

Connectivity

- with 2 independent binary inputs for potential-free contacts

Voltage

Operating voltage over bus 21...32 V DC

Electric current

Bus current consumption (data transfer) 12,5 mA

Measurement

Relative humidity 95 %

CO₂ measuring range 0 / 0,2 %

Detection

- up to 4 CO₂ limit values can be set
- compares measured temperature with the set temperature
- up to 2 humid limit values can be set

Materials

RAL colour RAL 9006 - White aluminium

Material Plastic/metal

Surface appearance matt

Type of surface treatment anodised

Dimensions

Installation height 1,5 m

Installation, mounting

Installation mode without spreader claws

Connection

- Connection bar with screw terminals for binary inputs
- bus connection via connecting terminal

Cable

Binary cable length	5 m
---------------------	-----

Settings

Supported configuration modes	system
-------------------------------	--------

Equipment

Product type:	product type: thermostat
<ul style="list-style-type: none">- heating or cooling possible in 2 stages- for heating or cooling mode- for single room control	

Use

Differentiation characteristic 3 - Sales	with integral bus coupling unit
--	---------------------------------

Safety

Halogen free	no
<ul style="list-style-type: none">- with dismantling protection	

Use conditions

Operating temperature	-5...45 °C
Energy efficiency class	IV (2%)
<ul style="list-style-type: none">- An alarm is signalled when the dewpoint is reached in order to prevent the formation of mould e.g. on cooling ceilings or in winter gardens	

temperatur

Temperature measuring range, linear	-5...45 °C
-------------------------------------	------------

Identification

Application, usage	KNX - sensors
Product family	Product family: heating, ventilation, air conditioning
Main design line	KNX - Berker K.1/K.5
Secondary design line(s)	KNX, Berker K.1, Berker K.5

Instructions

Information text	Recommendation: use deep box.
------------------	-------------------------------