



421209



IP44

SCHUKO socket outlet with cover plate and hinged cover Lock - differing lockings, with screw terminals, Splash-protected flush-mounted IP44, polar white glossy

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Full cover plate
-------	------------------

Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	glossy

Dimensions

Insertion depth	32 mm
-----------------	-------

Installation, mounting

Installation mode	without spreader claws, for single mounting, for screw fastening
-------------------	--

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with screw terminals	

Accessories included

- with flush-mounted box

Equipment

- with sealing cup

Use

Differentiation characteristic 2 - Sales	Lock - differing lockings
Differentiation characteristic 3 - Sales	with screw terminals

Safety

IK protection code against mechanical impacts	05
Protection index IP	IP44
- without enhanced contact protection	
- with 2 keys	

Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Splash-protected flush-mounted IP44

Instructions

Information text	Spare keys and other closures (max. 24) on request.
- The locks of an article do have identical lockings. When ordering several articles those do usually have differing lockings.	