



50069940



**Push-button, change-over contact surface-mounted with lens, Surface-mounted, white glossy**

#### Technical features

#### Architecture

Type of control unit	rocker
----------------------	--------

#### Main electrical features

Nominal voltage	250 V
-----------------	-------

Rated voltage	250 V AC
---------------	----------

#### Electric current

Momentary-contact current	10 A
---------------------------	------

#### Materials

Colour of design line	white
-----------------------	-------

Colour independent of design lines	white
------------------------------------	-------

Colour	white
--------	-------

Colour	white
--------	-------

RAL colour	RAL 1013 - Oyster white
------------	-------------------------

Material	thermoplastic
----------	---------------

Surface appearance	glossy
--------------------	--------

#### Dimensions

Depth	41 mm
-------	-------

Height	61 mm
--------	-------

Width	61 mm
-------	-------

#### Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

- knock out opening for entry at top and bottom	
---	--

#### Connection

- with plug-in terminals	
--------------------------	--

#### Cable

- with line and duct entry	
----------------------------	--

#### Equipment

- |  |  |
|--|--|
| - for lighting and monitoring circuit                              |  |
| - can be illuminated using neon and glow lamp unit with N-terminal |  |

#### Use

Differentiation characteristic 2 - Sales	with lens
--	-----------

#### Safety

Protection index IP	IP20
---------------------	------

**Identification**

Application, usage	Dry surface-mounted installation
Main design line	Surface-mounted