




40009930



SCHUKO socket outlet surface-mounted with enhanced touch protection, Screw terminals, Surface-mounted, white glossy

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	surface-mounting

Configuration

- with hollow base

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Complete housing
-------	------------------

Materials

Colour independent of design lines	white
Colour	white
Colour	white
RAL colour	RAL 1013 - Oyster white
Material	duroplastic
Surface appearance	glossy

Installation, mounting

Installation mode	for screw fastening
- knock out opening for entry at top and bottom	

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with screw terminals	

Cable

- with line and duct entry

Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
Differentiation characteristic 3 - Sales	Screw terminals

Safety

IK protection code against mechanical impacts	02
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

Identification

Application, usage	Dry surface-mounted installation
Main design line	Surface-mounted
