



4040



3gang SCHUKO socket outlet, surface-mounted with screw terminals, Surface-mounted, white glossy

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	surface-mounting

Configuration

- with hollow base

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Complete housing
-------	------------------

Materials

Colour independent of design lines	white
Colour	white
Colour	white
RAL colour	RAL 1013 - Oyster white
Material	duroplastic
Surface appearance	glossy

Installation, mounting

Installation mode	for vertical and horizontal mounting, for screw fastening
-------------------	---

- knock out openings for entries at top, bottom and side

Connection

Conductor cross-section	1...2,5 mm ²
Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with screw terminals	

Use

Differentiation characteristic 3 - Sales	with screw terminals
--	----------------------

Safety

IK protection code against mechanical impacts	02
Protection index IP	IP20
- without enhanced contact protection	

Identification

Application, usage	Dry surface-mounted installation
Main design line	Surface-mounted
