



80141500



IP55

Group push-button module 2gang surface-mounted/flush-mounted with integral bus coupling unit, KNX - Berker W.1

Technical features

Architecture

Fixing mode	flush-mounting or surface-mounting
Technical version	2gang

Functions

- operating concept "independent push-button" function predefined
- operating concept for "roller shutter/blind" function predefined
- switching of scenes (1..8) possible
- brightness value of the status LED for day/nighttime operation preset, status LED for day/nighttime operation can be controlled via object
- push-button functions: including switching, dimming, roller shutter/blind, timer, priority, operating mode changeover
- colour of status LED is preset for the device
- Function for manual interruption of automatic functions already triggered
- operating surfaces as buttons (single-surface operation) and rockers (two-surface operation)
- the brightness of status LEDs are individually adjustable for button/ rocker function
- brightness value of the status LEDs for day/nighttime operation adjustable via object or manually
- button/rocker functions for switching, dimming, roller shutter/blind, value transmitter 1/2 byte, room thermostat extension unit, priority, scene, automatic control deactivation

Controls and indicators

- with programming button and red programming LED

Voltage

Operating voltage over bus	21...32 V DC
----------------------------	--------------

Electric current

Bus current consumption (data transfer)	max. 10 mA
---	------------

Materials

RAL colour	RAL 7035 - Light grey
Material	duroplastic
Surface appearance	matt
Type of surface treatment	untreated

Dimensions

Insertion depth	22 mm
Height	44 mm

LED control

LED	with red status LED
-----	---------------------

Connection

- with integral bus coupling unit
- bus connection via connecting terminal

Settings

Supported configuration modes	system, easy
-------------------------------	--------------

Equipment

Product type: product type: push-button general

Use

Differentiation characteristic 3 - Sales with integral bus coupling unit

Safety

Protection index IP IP20

Halogen free no

Use conditions

Operating temperature -40...30 °C

Identification

Application, usage Surface-mounted wet-room installation, Flush-mounted wet-room installation, KNX - operating systems

Product family product family: push-button

Main design line KNX - Berker W.1

Secondary design line(s) KNX, Berker W.1