




6768813525



IP55



Socket outlet with earthing pin and hinged cover surface-mounted with labelling field, enhanced contact protection, Berker W.1, grey/light grey matt

Technical features

Architecture

Fixing mode	surface-mounting
- 2pole + earth	

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Cover, door

Cover	Complete housing
-------	------------------

Materials

Colour of design line	light grey
Material	thermoplastic
Surface appearance	matt

Connection

Connection terminals	according to IEC 60884-1
- with plug-in terminals	

Cable

- with one entry for 2 cables and one entry for cable and tube
--

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Use

Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 2 - Sales	enhanced contact protection

Safety

Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- without enhanced contact protection	

Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

Identification

Main design line

Berker W.1
