



4763



SCHUKO socket outlet with hinged cover Lock - differing lockings, Splash-protected flush-mounted IP44, white glossy

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour independent of design lines	white
Colour	white
Colour	white
RAL colour	RAL 1013 - Oyster white
Material	thermoplastic
Surface appearance	glossy

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Use

Differentiation characteristic 2 - Sales	Lock - differing lockings
--	---------------------------

Safety

IK protection code against mechanical impacts	05
Protection index IP	IP44
- without enhanced contact protection	
- with 2 keys	

Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Splash-protected flush-mounted IP44

Instructions

Information text Spare keys and other closures (max. 24) on request.

- The locks of an article do have identical lockings.
When ordering several articles those do usually have differing lockings.
-