



4212



IP44

**SCHUKO socket outlet with cover plate and hinged cover Lock - differing lockings, with screw terminals, Splash-protected flush-mounted IP44, grey glossy**

#### Technical features

#### Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50 Hz
Rated current	16 A

#### Electric current

Rated current	16 A
---------------	------

#### Cover, door

Cover	Full cover plate
-------	------------------

#### Materials

Colour independent of design lines	Grey
Colour	light grey
Colour	grey
RAL colour	RAL 7035 - Light grey
Material	thermoplastic
Surface appearance	glossy

#### Dimensions

Insertion depth	32 mm
-----------------	-------

#### Installation, mounting

Installation mode	without spreader claws, for single mounting, for screw fastening
-------------------	--

#### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with screw terminals	

#### Accessories included

- with flush-mounted box
--------------------------

#### Equipment

- with sealing cup
--------------------

### Use

Differentiation characteristic 2 - Sales	Lock - differing lockings
Differentiation characteristic 3 - Sales	with screw terminals

### Safety

IK protection code against mechanical impacts	05
Protection index IP	IP44
- without enhanced contact protection	
- with 2 keys	

### Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Splash-protected flush-mounted IP44

### Instructions

Information text	Spare keys and other closures (max. 24) on request.
- The locks of an article do have identical lockings. When ordering several articles those do usually have differing lockings.	