



40009950



**SCHUKO socket outlet surface-mounted with screw terminals, Surface-mounted, white glossy**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	surface-mounting

**Configuration**

- without hollow base

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Complete housing
-------	------------------

**Materials**

Colour independent of design lines	white
Colour	white
Colour	white
RAL colour	RAL 1013 - Oyster white
Material	duroplastic
Surface appearance	glossy

**Installation, mounting**

Installation mode	for screw fastening
-	knock out opening for entry at top and bottom

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
-	with screw terminals

**Cable**

- with line and duct entry

**Use**

Differentiation characteristic 3 - Sales	with screw terminals
--	----------------------

**Safety**

---

IK protection code against mechanical impacts	02
Protection index IP	IP20
- without enhanced contact protection	

---

**Identification**

---

Application, usage	Dry surface-mounted installation
Main design line	Surface-mounted

---