




301240



**Control on/off switch 2pole with imprint "0" surface-mounted with red lens, Surface-mounted, white glossy**

Technical features

#### Architecture

Type of control unit	single rocker
Fixing mode	surface-mounting

#### Configuration

- 2pole

#### Controls and indicators

- No

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

#### Electric current

Switching current	10 AX (100 W Self Ballasted Lamp (SBL))
-------------------	---

#### Materials

Colour independent of design lines	white
Colour	white
Colour	white
RAL colour	RAL 1013 - Oyster white
Material	duroplastic
Surface appearance	glossy

#### Dimensions

Depth	42 mm
Height	61 mm
Width	61 mm

#### Fluorescent bulbs control

Neon lamp current	1 mA
-------------------	------

#### Installation, mounting

Installation mode	for screw fastening
-	knock out opening for entry at top and bottom

#### Connection

Type of connection	Quickconnect
-	with screw terminals

#### Cable

- with cable entry at top and bottom

---

**Equipment**

- with neon lamp unit with N terminal order no. 1675
  - for lighting and monitoring circuit
  - can be illuminated using neon and glow lamp unit with N-terminal
- 

**Use**

---

Differentiation characteristic 2 - Sales with red lens

---

**Safety**

---

Protection index IP IP20

---

**Identification**

---

Application, usage Dry surface-mounted installation

Main design line Surface-mounted

---