



47231907

SCHUKO socket outlet with "ZSV" imprint enhanced contact protection, Berker S.1/B.3/B.7, orange

Technical features

rch		

Design	according to DIN 49440
Fixing mode	flush-mounting
Technical version	Imprint "ZSV"

Connectivity

Type of USB port	other
Type of oob port	Other

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Rated current	16 A

Electric current

Rated current	16 A

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour of design line	orange
Colour	orange
Colour	orange
RAL colour	RAL 2003 - Pastel orange
Material	duroplastic
Surface appearance	matt
Material	

Dimensions

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

Installation, mounting

Installation mode	with clamp/screw fastening

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Equipment

With transparent product label holder	no
With transparent broduct laber holder	110

Use

Differentiation characteristic 2 - Sales	enhanced contact protection
--	-----------------------------



Safety

IK protection code against mecanical impacts	02
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	
Identification	
Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7
Instructions	
Information text	Insert colour-coded.