





SCHUKO socket outlet with "EDV" imprint enhanced contact protection, Berker S.1/B.3/B.7, red

Technical features

AICHILECTULE	Arc	hite	cture
--------------	-----	------	-------

Design	according to DIN 49440
Fixing mode	flush-mounting
Technical version	Imprint "EDV"

Connectivity

Type of USB port other

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Rated current	16 A

Electric current

Rated current 16 A

Cover, door

Cover Central cover plate

Materials

red
red
red
RAL 3003 - Ruby red
duroplastic
matt

Dimensions

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

Installation, mounting

Installation mode with clamp/screw fastening

Connection

Connection terminals according to IEC 60884-1

Connection terminals according to VDE 0620-1:2021-02

- with plug-in terminals

Equipment

With transparent product label holder no

Use

Differentiation characteristic 2 - Sales enhanced contact protection



Safety

IK protection code against mecanical impacts	02
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	
Identification	
Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7
Instructions	
Information text	Insert colour-coded.