



41516015



SCHUKO socket outlet with hinged cover, control LED and imprint "EDV" with hinged cover, enhanced contact protection, with screw-in lift terminals, Berker Q.1/Q.3/Q.7/Q.9, red velvety

Technical features

Architecture

| | |
|-------------------|----------------|
| Fixing mode | flush-mounting |
| Technical version | Imprint "EDV" |

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Electric current

| | |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

Cover, door

| | |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

Materials

| | |
|--------------------|---------------------|
| Colour | red |
| Colour | red |
| RAL colour | RAL 3003 - Ruby red |
| Material | thermoplastic |
| Surface appearance | velvety |

Installation, mounting

| | |
|-------------------|----------------------------|
| Installation mode | with clamp/screw fastening |
|-------------------|----------------------------|

Equipment

| | |
|---------------------------------------|----|
| With transparent product label holder | no |
|---------------------------------------|----|

Use

| | |
|--|------------------------------|
| Differentiation characteristic 1 - Sales | with hinged cover |
| Differentiation characteristic 2 - Sales | enhanced contact protection |
| Differentiation characteristic 3 - Sales | with screw-in lift terminals |

Safety

| | |
|---|---------------------------------|
| IK protection code against mechanical impacts | 05 |
| Protection index IP | IP20 |
| Enhanced contact protection | according to IEC 60884-1 |
| Enhanced contact protection | according to VDE 0620-1:2021-02 |
| - Enhanced contact protection | |

Identification

| | |
|--------------------------|--|
| Main design line | Berker Q.1/Q.3/Q.7/Q.9 |
| Secondary design line(s) | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |