



SCHUKO socket outlet with "ZSV" imprint enhanced contact protection, Berker Q.1/Q.3/Q.7/Q.9, orange

Technical features

rch		

Design	according to DIN 49440
Fixing mode	flush-mounting
Technical version	Imprint "ZSV"

Connectivity

Type of USB port	other
Type of oob port	Other

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Rated current	16 A

Electric current

Rated current	16 A

Cover, door

Cover	Central cover plat	ite
-------	--------------------	-----

Materials

orange
orange
orange
RAL 2003 - Pastel orange
thermoplastic
velvety

Dimensions

Installation depth, flush-mounted boxes	31 mm
---	-------

Installation, mounting

Installation mode	with clamp/screw fastening
-------------------	----------------------------

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

- with plug-in terminals

Equipment

no
nc

Use



Safety

IK protection code against mecanical impacts	05
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	
Identification	
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9
Instructions	
Information text	Insert colour-coded.