



75010018



IP20

quickconnect

## KNX Power supply 640 mA RMD with labelling field

### Technical features

#### Architecture

Bus system	EIB
Fixing mode	REG

#### Connectivity

- one output 640 mA incl. choke

#### Main electrical features

Frequency	50/60 Hz
-----------	----------

#### Voltage

Output voltage	28...32 V
----------------	-----------

#### Electric current

Output current	max. 640 mA
Output intensity	640 mA

#### Fuse

Fuse	with electronic short-circuit and overload protection
------	---

#### Materials

Colour	light grey
RAL colour	RAL 7035 - Light grey

#### Dimensions

Depth of installed product	64 mm
Height of installed product	90 mm
Length	64 mm
Width of installed product	72 mm

#### LED control

LED	with red LED for display of short-circuit and overload protection per output, with green LED for display of power supply
-----	--

#### Connection

Connection cross-sect. flexible conductor	0,75 / 2,5mm <sup>2</sup>
Connection cross-sect. rigid cable	0,75 / 2.5mm <sup>2</sup>
Conductor cross-section (flexible)	0,75...2,5 mm <sup>2</sup>
Conductor cross-section (rigid)	0,75...2,5 mm <sup>2</sup>
Connection	protected earth conductor must be connected
-	with QuickConnect plug-in terminals

#### Use

Differentiation characteristic 1 - Sales	with labelling field
--	----------------------

**Safety**

---

Protection index IP	IP20
---------------------	------

---

**Use conditions**

---

Operating temperature	-5...45 °C
-----------------------	------------

---

Storage/transport temperature	-20...70 °C
-------------------------------	-------------

---