



75010019



KNX Power supply 2 x 320 mA RMD with labelling field

Technical features

Architecture

Bus system EIB

Fixing mode REG

Connectivity

- with 2 outputs incl. choke per output

Main electrical features

Frequency 50/60 Hz

Voltage

Output voltage 28...32 V

Electric current

Output current max. 320 mA

Output intensity 320 mA

Fuse

Fuse with electronic short-circuit and overload protection

Materials

Colour light grey

RAL colour RAL 7035 - Light grey

Dimensions

Depth of installed product 64 mm

Height of installed product 90 mm

Length 64 mm

Width of installed product 72 mm

LED control

LED with red LED for display of short-circuit and overload protection per output, with green LED for display of power supply per output

Connection

Connection cross-sect. flexible conductor 0,75 / 2,5mm²

Connection cross-sect. rigid cable 0,75 / 2.5mm²

Conductor cross-section (flexible) 0,75...2,5 mm²

Conductor cross-section (rigid) 0,75...2,5 mm²

Connection protected earth conductor must be connected

- with plug-in terminals

Use

Differentiation characteristic 1 - Sales with labelling field

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

Storage/transport temperature	-20...70 °C
-------------------------------	-------------
