



41516013



**SCHUKO socket outlet with hinged cover, control LED and imprint "SV" with hinged cover, enhanced contact protection, with screw-in lift terminals, Berker Q.1/Q.3/Q.7/Q.9, green velvety**

Technical features

**Architecture**

|                   |                |
|-------------------|----------------|
| Fixing mode       | flush-mounting |
| Technical version | Imprint "SV"   |

**Main electrical features**

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

**Electric current**

|               |      |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

**Cover, door**

|       |                     |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

**Materials**

|                    |                       |
|--------------------|-----------------------|
| Colour             | green                 |
| Colour             | green                 |
| RAL colour         | RAL 6029 - Mint green |
| Material           | thermoplastic         |
| Surface appearance | velvety               |

**Installation, mounting**

|                   |                            |
|-------------------|----------------------------|
| Installation mode | with clamp/screw fastening |
|-------------------|----------------------------|

**Equipment**

|                                       |    |
|---------------------------------------|----|
| With transparent product label holder | no |
|---------------------------------------|----|

**Use**

|  |                              |
|--|------------------------------|
| Differentiation characteristic 1 - Sales | with hinged cover            |
| Differentiation characteristic 2 - Sales | enhanced contact protection  |
| Differentiation characteristic 3 - Sales | with screw-in lift terminals |

**Safety**

|   |                                 |
|---|---------------------------------|
| IK protection code against mechanical impacts | 05                              |
| Protection index IP                           | IP20                            |
| Enhanced contact protection                   | according to IEC 60884-1        |
| Enhanced contact protection                   | according to VDE 0620-1:2021-02 |
| - Enhanced contact protection                 |                                 |

**Identification**

|                          |  |
|--------------------------|--|
| Main design line         | Berker Q.1/Q.3/Q.7/Q.9                         |
| Secondary design line(s) | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |