



3036



Change-over switch Light control

Technical features

Architecture

| | |
|----------------------|----------------|
| Type of control unit | single rocker |
| Fixing mode | flush-mounting |

Functions

| | |
|-----------------|-------|
| Switching angle | 3,5 ° |
|-----------------|-------|

Configuration

- Off/change-over

Controls and indicators

- No

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |

Electric current

| | |
|-------------------|---|
| Switching current | 10 AX (100 W Self Ballasted Lamp (SBL)) |
|-------------------|---|

Materials

| | |
|--------------------|---------------|
| Material | Plastic/metal |
| Surface appearance | mat |

Dimensions

| | |
|-----------------|-------|
| Depth | 42 mm |
| Insertion depth | 31 mm |
| Height | 71 mm |
| Width | 71 mm |

Installation, mounting

| | |
|-------------------|--|
| Installation mode | with spreader claws, for screw fastening |
|-------------------|--|

Connection

| | |
|--------------------------|--------------------------|
| Connection terminals | according to IEC 60669-1 |
| Connection terminals | according to VDE 0632-1 |
| Type of connection | Quickconnect |
| - with plug-in terminals | |

Equipment

- for lighting and monitoring circuit

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
| Impact strength | IK07 |

Identification

| | |
|-----------------------|-----------------------------|
| Application, usage | HVAC control, Light control |
| Appliance switch type | No |
| Main design line | Light control |

Instructions

| | |
|------------------|--|
| Information text | spreader claws, insulated to the supporting ring, self-resetting |
|------------------|--|

- A control change-over switch is shown here as an example. With 2-pole and 3-pole control on/off switches, other rocker switches and neon lamp units are required.
-