



ε



IP20

Touch dimmer (R, L) Electronics platform

Technical features

Functions

- when cover is detached, the switch status is retained (wallpaper function)
- bulb-preserving soft startup

Main electrical features

Frequency	50/60 Hz
-----------	----------

Voltage

Operating voltage	230 V AC
-------------------	----------

Fuse

Fuse	short-circuit and overload proof (electronic fuse)
------	--

Power

Dimmable conventional transformers	25...400 VA
Power consumption (standby)	< 0,3 W

Measurement

Relative humidity (without condensation)	0...65 % (without condensation)
Extension unit input	with extension unit input for push-button (NO contact), single-surface operation and motion detector extension unit

Materials

Colour	not applicable
Material	Plastic/metal

- no conductive connection between supporting ring and spreading claws

Dimensions

Insertion depth	32 mm
-----------------	-------

Incandescent bulbs control

230 V incandescent lamps and halogen lamps	25...400 W
--	------------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Screw terminals (max.)	2 x 1,5/1 x 2,5 mm ²
Number of substations	unlimited

- with screw terminals

Cable

Load cable length	max. 100 m
Cable length, extensions	max. 50 m

Equipment

- phase cut-on
 - switch-on brightness level can be stored safe after power failure
-

Use conditions

- Operating temperature -5...45 °C
- low intrinsic energy requirement
-

Identification

- Application, usage Motion detector, Light control, KNX radio- operating systems
- Main design line Electronics platform
-