



6765102045



**Socket outlet with earthing pin and LED orientation light enhanced contact protection, Screw-in lift terminals, Serie R.classic, black glossy**

Technical features

**Architecture**

Fixing mode	flush-mounting
- 2pole + earth	

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Power**

Power consumption	0.25 W/0.35 VA
-------------------	----------------

**Cover, door**

Cover	Central cover plate
-------	---------------------

**Detection**

- integrated brightness sensor that switches the orientation light on at twilight and off when there is sufficient brightness

**Materials**

Colour of design line	black
Colour	black
Colour	black
RAL colour	RAL 9005 - Jet black
Material	thermoplastic
Surface appearance	glossy

**Lighting control**

Switch-off brightness	≈ 4 lx
Switch-on brightness	≈ 2 lx
Light intensity (white)	0,2 cd

**LED control**

LED	long service life of the LED, white LED light
-----	---

**Installation, mounting**

Installation mode	with spreader claws
-------------------	---------------------

**Connection**

Conductor cross-section (rigid)	max. 2,5 mm <sup>2</sup>
Connection terminals	according to IEC 60884-1
- with screw-in lift terminals	

---

**Cable**

- through-wiring possible, therefore also ideal for retrofitting
- 

**Equipment**

- additional benefit by combination of a socket outlet with an orientation light
- 

**Use**

---

Differentiation characteristic 2 - Sales	enhanced contact protection
Differentiation characteristic 3 - Sales	Screw-in lift terminals

---

**Safety**

- 
- |                             |                          |
|-----------------------------|--------------------------|
| Enhanced contact protection | according to IEC 60884-1 |
|-----------------------------|--------------------------|
- Enhanced contact protection
- 

**Identification**

---

Main design line	Serie R.classic
------------------	-----------------

---

**Instructions**

---

Information text	Caution! Items with special flush-mounted insert. Centre plates with LED orientation lights are not compatible with the standard socket outlets.
------------------	---

---