



47292045



## Double SCHUKO socket outlet with cover plate enhanced contact protection, Berker R.1, black glossy

### Technical features

#### Architecture

|             |                        |
|-------------|------------------------|
| Design      | according to DIN 49440 |
| Fixing mode | flush-mounting         |

#### Main electrical features

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

#### Electric current

|               |      |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

#### Cover, door

|       |                  |
|-------|------------------|
| Cover | Full cover plate |
|-------|------------------|

#### Materials

|                       |                      |
|-----------------------|----------------------|
| Colour of design line | black                |
| Colour                | black                |
| Colour                | deep black           |
| RAL colour            | RAL 9005 - Jet black |
| Material              | thermoplastic        |
| Surface appearance    | glossy               |

#### Dimensions

|                   |       |
|-------------------|-------|
| Assembling height | 22 mm |
|-------------------|-------|

#### Installation, mounting

|                                      |                          |
|--------------------------------------|--------------------------|
| For installation in 1gang wall boxes | according to DIN 49073-1 |
| Installation mode                    | with spreader claws      |

#### Connection

|                          |                                 |
|--------------------------|---------------------------------|
| Connection terminals     | according to IEC 60884-1        |
| Connection terminals     | according to VDE 0620-1:2021-02 |
| - with plug-in terminals |                                 |

#### Use

|  |                             |
|--|-----------------------------|
| Differentiation characteristic 2 - Sales | enhanced contact protection |
|--|-----------------------------|

#### Safety

|   |                                 |
|---|---------------------------------|
| IK protection code against mechanical impacts | 05                              |
| Protection index IP                           | IP20                            |
| Enhanced contact protection                   | according to IEC 60884-1        |
| Enhanced contact protection                   | according to VDE 0620-1:2021-02 |
| - Enhanced contact protection                 |                                 |

**Identification**

---

Main design line

Berker R.1

---