



6765092022



Socket outlet with earthing pin and control LED with enhanced touch protection, Screw-in lift terminals, Berker R.1/R.3/R.8, red glossy

Technical features

Architecture

| | |
|-----------------|----------------|
| Fixing mode | flush-mounting |
| - 2pole + earth | |

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Cover, door

| | |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

Materials

| | |
|------------------------------|---------------------|
| Colour of labelling | 217,217,217 |
| Design lines special colours | red |
| Colour | red |
| Colour | red |
| RAL colour | RAL 3003 - Ruby red |
| Material | thermoplastic |
| Material for printing | ABS red |
| Surface appearance | glossy |

Dimensions

| | |
|-----------------|-------|
| Insertion depth | 32 mm |
|-----------------|-------|

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

Connection

| | |
|--------------------------------|--------------------------|
| Connection terminals | according to IEC 60884-1 |
| - with screw-in lift terminals | |

Equipment

| | |
|-----------------------|------------|
| Type of configuration | Laserdruck |
|-----------------------|------------|

Use

| | |
|--|--------------------------------|
| Differentiation characteristic 2 - Sales | with enhanced touch protection |
| Differentiation characteristic 3 - Sales | Screw-in lift terminals |

Safety

| | |
|---|--------------------------|
| IK protection code against mechanical impacts | 05 |
| Enhanced contact protection | according to IEC 60884-1 |
| - Enhanced contact protection | |

Identification

| | |
|--------------------------|------------------------------------|
| Main design line | Berker R.1/R.3/R.8 |
| Secondary design line(s) | Berker R.1, Berker R.3, Berker R.8 |

Instructions

| | |
|------------------|----------------------|
| Information text | Insert colour-coded. |
|------------------|----------------------|
