



47748982



Double SCHUKO socket outlet with cover plate, high Berker S.1/B.3/B.7, white glossy

Technical features

Architecture

| | |
|-------------|----------------|
| Fixing mode | flush-mounting |
|-------------|----------------|

Connectivity

| | |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Electric current

| | |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

Cover, door

| | |
|-------|------------------|
| Cover | Full cover plate |
|-------|------------------|

Materials

| | |
|-----------------------|-------------------------|
| Colour of design line | polar white |
| Colour | white |
| Colour | white |
| RAL colour | RAL 1013 - Oyster white |
| Material | duroplastic |
| Surface appearance | glossy |

Installation, mounting

| | |
|--------------------------------------|----------------------------|
| For installation in 1gang wall boxes | according to DIN 49073-1 |
| Installation mode | with clamp/screw fastening |

Equipment

| | |
|---------------------------------------|----|
| With transparent product label holder | no |
|---------------------------------------|----|

Safety

| | |
|---|------|
| IK protection code against mechanical impacts | IK02 |
| Protection index IP | IP20 |
| <ul style="list-style-type: none"> - without enhanced contact protection - integrated earth handle in cover frame provides protection against soiling during painting and renovation work | |

Identification

| | |
|--------------------------|------------------------------------|
| Main design line | Berker S.1/B.3/B.7 |
| Secondary design line(s) | Berker S.1, Berker B.3, Berker B.7 |

Instructions

Information text

Caution!

The cover plate with earth handle must be installed prior to commissioning.