


47506003



## SCHUKO socket outlet with labelling field, Berker Q.1/Q.3/Q.7/Q.9, green velvety

### Technical features

#### Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

#### Connectivity

Type of USB port	other
------------------	-------

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Electric current

Rated current	16 A
---------------	------

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Design lines special colours	green
Colour	green
Colour	green
RAL colour	RAL 6029 - Mint green
Material	duroplastic
Surface appearance	velvety

#### Dimensions

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

#### Use

Differentiation characteristic 1 - Sales	with labelling field
--	----------------------

---

**Safety**

---

IK protection code against mechanical impacts	02
Protection index IP	IP20
- without enhanced contact protection	

---

**Identification**

---

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

---

**Instructions**

---

Information text	Insert colour-coded. 1140.
------------------	----------------------------

---

Labelling field height designed for 6 mm P-touch strips.