



47516049



SCHUKO socket outlet with hinged cover and "ZSV" imprint in orange Berker Q.1/Q.3/Q.7/Q.9, polar white velvety

Technical features

Architecture

| | |
|-------------------|-------------------------|
| Design | according to DIN 49440 |
| Fixing mode | flush-mounting |
| Technical version | Imprint "ZSV" in orange |

Connectivity

| | |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Electric current

| | |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

Cover, door

| | |
|-------------------------------------|---------------------|
| Cover | Central cover plate |
| - with hinged cover that falls back | |

Materials

| | |
|-----------------------|-----------------------|
| Colour of design line | polar white |
| Colour | polarwhite |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Material | duroplastic |
| Surface appearance | velvety |

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

Connection

| | |
|--------------------------|---------------------------------|
| Connection terminals | according to IEC 60884-1 |
| Connection terminals | according to VDE 0620-1:2021-02 |
| - with plug-in terminals | |

Safety

| | |
|---|------|
| IK protection code against mechanical impacts | 02 |
| Protection index IP | IP20 |
| - without enhanced contact protection | |

Identification

| | |
|--------------------------|--|
| Main design line | Berker Q.1/Q.3/Q.7/Q.9 |
| Secondary design line(s) | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |
