



20306086



**Temperature controller, NC contact, with centre plate with rocker switch, Berker Q.1/Q.3/Q.7/Q.9, anthracite velvety, lacquered**

Technical features

**Functions**

- with on/off switch and indicator LED for "on"

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz

**Electric current**

Inductive load at $\cos \varphi = 0.6$	max. 4 A
Switching current "Heating" at $\cos \varphi = 0.6$	4 A
Heating switching current	10 A
Switching current	10 A

**Measurement**

Range of temperatures	5 / 30 °C
-----------------------	-----------

**Materials**

Colour of design line	anthracite
Colour	anthracite
Material / workmanship	lacquered
Material	Plastic/metal

**Dimensions**

Insertion depth	24,5 mm
-----------------	---------

**Installation, mounting**

Installation mode	without spreader claws
-------------------	------------------------

**Connection**

Connection	with separate connection for night lowering
- with plug-in terminals	

**Equipment**

Night lowering	≈ 4 K
Switching temperature difference	≈ 0,5 K
- setting knob with temperature range limitation	
- e.g. for valve drives closed in de-energised state	

**Use**

Differentiation characteristic 1 - Sales	with rocker switch
--	--------------------

**Use conditions**

---

Energy efficiency class	I (1%)
- with thermal return	

---

**temperatur**

---

Temperature	5...30 °C
-------------	-----------

---

**Identification**

---

Application, usage	HVAC control
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

---