product sheet 20346086





20346086



Functions	
- with on/off switch and 2 LEDs	
Main electrical features	
Nominal voltage	230
Rated voltage	230 V A(
Frequency	50/60 H
Electric current	
Switching current	10 /
Materials	
Colour of design line	anthracit
Colour	anthracit
Material / workmanship	lacquere
Material	Plastic/meta
LED control	
	with LED for heating and LED for night lowerin
LED Installation, mounting Installation mode	
Installation, mounting Installation mode Connection	without spreader claw
Installation, mounting Installation mode Connection Sensor cable length	without spreader claw 4 r
Installation, mounting Installation mode Connection Sensor cable length Connection	without spreader claw 4 r
Installation, mounting Installation mode Connection Sensor cable length Connection - with plug-in terminals	without spreader claw 4 r
Installation, mounting Installation mode Connection Sensor cable length Connection - with plug-in terminals Settings	without spreader claw 4 r with separate connection for night lowerin
Installation, mounting Installation mode Connection Sensor cable length Connection - with plug-in terminals Settings Floor temperature setting range	
Installation, mounting Installation mode Connection Sensor cable length Connection - with plug-in terminals Settings Floor temperature setting range Room temperature setting range	without spreader claw 4 r with separate connection for night lowerin 1050 °
Installation, mounting Installation mode Connection Sensor cable length Connection - with plug-in terminals Settings Floor temperature setting range Room temperature setting range Equipment	without spreader claw 4 r with separate connection for night lowerin 1050 ° 530 °
Installation, mounting Installation mode Connection Sensor cable length Connection - with plug-in terminals Settings Floor temperature setting range Room temperature setting range Equipment Night lowering	without spreader claw 4 r with separate connection for night lowerin 1050 ° 530 °
Installation, mounting Installation mode Connection Sensor cable length Connection - with plug-in terminals Settings Floor temperature setting range Room temperature setting range Equipment Night lowering Switching temperature difference	without spreader claw 4 r with separate connection for night lowerin 1050 ° 530 °
Installation, mounting Installation mode Connection Sensor cable length	without spreader claw 4 r with separate connection for night lowerin 1050 ° 530 °
Installation, mounting Installation mode Connection Sensor cable length Connection - with plug-in terminals Settings Floor temperature setting range Room temperature setting range Equipment Night lowering Switching temperature difference - setting knob with temperature range limitation - e.g. for valve drives closed in de-energised state	without spreader claw 4 r with separate connection for night lowerin 1050° 530°
Installation, mounting Installation mode Connection Sensor cable length Connection - with plug-in terminals Settings Floor temperature setting range Room temperature setting range Equipment Night lowering Switching temperature difference - setting knob with temperature range limitation	without spreader claw 4 r with separate connection for night lowerin 1050 °

Thermostat, NO contact, with centre plate, for underfloor heating with rocker switch, external temperature sensor, Berker Q.1/Q.3/Q.7/Q.9, anthracite velvety, lacquered



Use conditions Energy efficiency class I (1%) - with thermal return Identification Application, usage HVAC control Main design line Berker Q.1/Q.3/Q.7/Q.9

Secondary design line(s)

Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9