



41436013



SCHUKO socket outlet with screw-in lift terminals, Berker Q.1/Q.3/Q.7/Q.9, green velvety

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Design lines special colours	green
Colour	green
Colour	green
RAL colour	RAL 6029 - Mint green
Material	duroplastic
Surface appearance	velvety

Dimensions

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
-	with screw-in lift terminals

Use

Differentiation characteristic 3 - Sales	with screw-in lift terminals
--	------------------------------

Safety

IK protection code against mechanical impacts	02
Protection index IP	IP20
- without enhanced contact protection	

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

Instructions

Information text	Insert colour-coded.
------------------	----------------------
