



47516089



**SCHUKO socket outlet with hinged cover enhanced contact protection, Berker Q.1/Q.3/Q.7/Q.9, polar white velvety**

Technical features

#### Architecture

|             |                        |
|-------------|------------------------|
| Design      | according to DIN 49440 |
| Fixing mode | flush-mounting         |

#### Connectivity

|                  |       |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

#### Main electrical features

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

#### Electric current

|               |      |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

#### Cover, door

|                                   |                     |
|-----------------------------------|---------------------|
| Cover                             | Central cover plate |
| - with self-closing hinged covers |                     |

#### Materials

|                       |                       |
|-----------------------|-----------------------|
| Colour of design line | polar white           |
| Colour                | polarwhite            |
| Colour                | white                 |
| RAL colour            | RAL 9010 - Pure white |
| Material              | duroplastic           |
| Surface appearance    | velvety               |

#### Installation, mounting

|                   |                     |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

#### Connection

|                          |                                 |
|--------------------------|---------------------------------|
| Connection terminals     | according to IEC 60884-1        |
| Connection terminals     | according to VDE 0620-1:2021-02 |
| - with plug-in terminals |                                 |

#### Use

|  |                             |
|--|-----------------------------|
| Differentiation characteristic 2 - Sales | enhanced contact protection |
|--|-----------------------------|

---

**Safety**

---

|   |                                 |
|---|---------------------------------|
| IK protection code against mechanical impacts | 02                              |
| Protection index IP                           | IP20                            |
| Enhanced contact protection                   | according to IEC 60884-1        |
| Enhanced contact protection                   | according to VDE 0620-1:2021-02 |
| - Enhanced contact protection                 |                                 |

---

**Identification**

---

|                          |  |
|--------------------------|--|
| Application, usage       | Flush-mounted wet-room installation            |
| Main design line         | Berker Q.1/Q.3/Q.7/Q.9                         |
| Secondary design line(s) | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |

---

**Instructions**

- 
- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing set (order no. 10107200).
-