



47526059



SCHUKO socket outlet with hinged cover and "EDV" imprint in red Labelling field, enhanced contact protection, Berker Q.1/Q.3/Q.7/Q.9, polar white velvety

Technical features

Architecture

| | |
|-------------------|------------------------|
| Design | according to DIN 49440 |
| Fixing mode | flush-mounting |
| Technical version | Imprint "EDV" in red |

Connectivity

| | |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Electric current

| | |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

Cover, door

| | |
|-------|---------------------------------|
| Cover | Central cover plate |
| - | with self-closing hinged covers |

Materials

| | |
|-----------------------|-----------------------|
| Colour of design line | polar white |
| Colour | polarwhite |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Material | duroplastic |
| Surface appearance | velvety |

Dimensions

| | |
|-----------------|-------|
| Insertion depth | 32 mm |
|-----------------|-------|

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

Connection

| | |
|----------------------|---------------------------------|
| Connection terminals | according to IEC 60884-1 |
| Connection terminals | according to VDE 0620-1:2021-02 |
| - | with plug-in terminals |

Use

| | |
|--|-----------------------------|
| Differentiation characteristic 1 - Sales | Labelling field |
| Differentiation characteristic 2 - Sales | enhanced contact protection |

Safety

| | |
|--|---------------------------------|
| IK protection code against mechanical impacts | 02 |
| Protection index IP | IP44 |
| Enhanced contact protection | according to IEC 60884-1 |
| Enhanced contact protection | according to VDE 0620-1:2021-02 |
| - enhanced contact protection VDE 0620-1:2021-02 | |

Identification

| | |
|--------------------------|--|
| Application, usage | Flush-mounted wet-room installation |
| Main design line | Berker Q.1/Q.3/Q.7/Q.9 |
| Secondary design line(s) | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |

Instructions

| | |
|---|--|
| Information text | Labelling field height arranged for P-touch strips 6 mm. |
| - Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set. | |