



41516014



SCHUKO socket outlet with hinged cover, control LED and imprint "ZSV" with hinged cover, enhanced contact protection, with screw-in lift terminals, Berker Q.1/Q.3/Q.7/Q.9, orange velvety

Technical features

Architecture

Fixing mode	flush-mounting
Technical version	Imprint "ZSV"

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour	orange
Colour	orange
RAL colour	RAL 2003 - Pastel orange
Material	thermoplastic
Surface appearance	velvety

Installation, mounting

Installation mode	with clamp/screw fastening
-------------------	----------------------------

Equipment

With transparent product label holder	no
---------------------------------------	----

Use

Differentiation characteristic 1 - Sales	with hinged cover
Differentiation characteristic 2 - Sales	enhanced contact protection
Differentiation characteristic 3 - Sales	with screw-in lift terminals

Safety

IK protection code against mechanical impacts	05
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9