



6765118989



**Socket outlet with earthing pin and hinged cover with enhanced touch protection, with lock - differing lockings, with screw-in lift terminals, Berker S.1/B.3/B.7, polar white glossy**

#### Technical features

#### Architecture

|                 |                |
|-----------------|----------------|
| Fixing mode     | flush-mounting |
| - 2pole + earth |                |

#### Main electrical features

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

#### Cover, door

|       |                     |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

#### Materials

|                       |                       |
|-----------------------|-----------------------|
| Colour of design line | polar white           |
| Colour                | polarwhite            |
| Colour                | white                 |
| RAL colour            | RAL 9010 - Pure white |
| Material              | thermoplastic         |
| Surface appearance    | glossy                |

#### Installation, mounting

|                   |                     |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

#### Connection

|                      |                          |
|----------------------|--------------------------|
| Connection terminals | according to IEC 60884-1 |
|----------------------|--------------------------|

#### Use

|  |                                |
|--|--------------------------------|
| Differentiation characteristic 1 - Sales | with enhanced touch protection |
| Differentiation characteristic 2 - Sales | with lock - differing lockings |
| Differentiation characteristic 3 - Sales | with screw-in lift terminals   |

#### Safety

|   |    |
|---|----|
| IK protection code against mechanical impacts | 05 |
| - without enhanced contact protection         |    |

#### Identification

|                          |                                    |
|--------------------------|------------------------------------|
| Main design line         | Berker S.1/B.3/B.7                 |
| Secondary design line(s) | Berker S.1, Berker B.3, Berker B.7 |

#### Instructions

|                  |   |
|------------------|---|
| Information text | Spare keys and other closures (max. 24) on request. |
|------------------|---|